



Th. WORTELBOER B.V.

P.O BOX 5 - NL - 6580 AA MALDEN

HOLLAND

PHONE 31 - 24 - 358 65 14

FAX 31 - 24 - 358 70 79

www.wortelboer.ws

E-mail : info@wortelboer.ws

Pipe stoppers 1024

for testing under pressure of all kinds of pipes

At the threading end of the stoppers a T-joint could be placed for attaching a tap for venting the air, a manometer and a pressure hose.

After using the stoppers, the rubber seal (gas and oil resistant) will return to its original form, through which a permanent use is assured.

The stoppers can resist a pressure up to 12 bar for the small sizes.

The stoppers have to be secured for safety.

Max. pressure range:

Ø 12 - 78 mm. 12 bar

Ø 84 - 158 mm. 8 bar

Ø165 - 600 mm. 6 bar



| Ø Stopper mm | Effective working range mm |
|--------------|----------------------------|
| 12 | +2 |
| 15 | +2 |
| 18 | +2 |
| 19 | +2 |
| 20 | +2 |
| 22 | +2 |
| 24 | +2 |
| 25 | +2 |
| 26 | +2 |
| 28 | +2 |
| 30 | +2 |
| 32 | +2 |
| 34 | +2 |
| 35 | +3 |
| 38 | +3 |
| 40 | +3 |
| 42 | +3 |
| 45 | +3 |
| 48 | +3 |
| 50 | +3 |
| 53 | +3 |
| 57 | +3 |
| 63 | +3 |
| 65 | +3 |
| 69 | +3 |
| 74 | +4 |
| 78 | +4 |
| 84 | +4 |
| 94 | +5 |
| 98 | +5 |
| 102 | +5 |
| 106 | +5 |
| 115 | +5 |
| 122 | +5 |
| 126 | +5 |
| 130 | +5 |
| 140 | +5 |
| 144 | +5 |
| 148 | +5 |

Larger on request.