



Th. WORTELBOER B.V.

P.O BOX 5 - NL - 6580 AA MALDEN

HOLLAND

PHONE 31 - 24 - 358 65 14

FAX 31 - 24 - 358 70 79

www.wortelboer.ws

E-mail : info@wortelboer.ws

PIPE NOTCHERS

AL100 and AL150



The quality of welded pipe constructions is determined largely by correct preparation. Introducing the pipe notcher by ALMI offers accurate one step tube section-ends preparation in seconds with minimal setup and changeover time. Simply position a tube section in the rotatable clamp mounted on the carriage and grind a diameter and/or shape of a tube section accurately and efficiently to a desired angle.

GRINDING: FAST AND ECONOMICAL

With the ALMI pipe notcher you always have the correct belt speed for every diameter and type of material. The ALMI pipe notcher reduces machining time to a minimum.

ANY DIAMETER

ALMI supplies a wide range of grinding rollers: from 20 mm. to 114,3 mm. in diameter, increasing per step in 2 mm.

ANY ANGLE

The compound table with carriage is infinitely variable. This means that all your tube sections can be ground at any angle between 90 degrees and 30 degrees.

ALL AVAILABLE MATERIALS

The ALMI pipe notcher grinds square, rectangular and circular tube sections. Suitable for all types of material thicknesses and material.

CHANGING A ROLLER IS FAST AND SIMPLE !

The ALMI pipe notching machine is designed so that the grinding roller and grinding belt are easy to change. Setting up a new diameter takes less than two minutes.





AL100U operated with level		
Band	mm	100 x 2.000
Motor	Kw	3.0
Rotation speed	t/min.	2.905
Belt speed	m/sec.	30
Grinding	Ø mm	Ø 20 - Ø 76
Weight	kg	190
Measurements	l x b x h	1450 x 1200 x 650



AL100U-02 operated with level or handwheel		
Band	mm	100 x 2.000
Motor	Kw	3.0
Rotation speed	t/min.	2.905
Belt speed	m/sec.	30
Grinding	Ø mm	Ø 20 - Ø 76
Weight	kg	210
Measurements	l x b x h	1450 x 1200 x 650



AL100 operated with handwheel		
Band	mm	100 x 2.000
Motor	Kw	3.0
Rotation speed	t/min.	2.905
Belt speed	m/sec.	30
Grinding	Ø mm	Ø 20 - Ø 76
Weight	kg	230
Measurements	l x b x h	1450 x 1150 x 650



AL150 operated with handwheel		
Band	mm	150 x 2.000
Motor	Kw	4.0
Rotation speed	t/min.	2.905
Belt speed	m/sec.	30
Grinding	Ø mm	Ø 20 - Ø 114.3
Weight	kg	270
Measurements	l x b x h	1450 x 1200 x 850