

P.O BOX 5 - NL - 6580 AA MALDEN HOLLAND PHONE 31 - 24 - 358 65 14 FAX 31 - 24 - 358 70 79

www.wortelboer.ws

E-mail : info@wortelboer.ws

RIM and ULTRA RIM clamps

PIPE ADJUSTING- and REFORMING CLAMPS

for Pipes with diameters 4" - 72"+ standard



For both kinds of RIM Clamps:

- Available for pipe sizes 4" 72"+
- Reform high tensile strength pipe up to X80 and above with up to 25 mm. wall thickness
- For out-of-round conditions up to 50 mm.
- Galvanized jackscrews with pivoting pads
- Heavy Duty latching mechanism
- Jackscrew setting gauge make initial set-up easy.
- Torque wrench supplied for accurate reforming pressure
- ULTRA-RIM are AS STRONG (or more) AS MEGA-RIM

The RIM and ULTRA RIM Clamp series are designed to take on some of the toughest reforming jobs in the industry. These clamps make easy work of aligning and reforming. The standard RIM clamp is capable of reforming X45 - Sched. 80 with out-of-round conditions up to 50 mm. (depending of the pipe diameter).

The ULTRA RIM Clamp readily reforms high tensile strength pipe X-80 and above with up to 25 mm. wall thickness and out-of-round conditions up to some 55 mm. (dependent of the diameter). For versatility and strength, the RIM Clamp or ULTRA RIM Clamp is your choice

