



Th. WORTELBOER B.V.

SLUISWEG 9 - NL - 6582 AG HEUMEN

POSTBUS 5 - NL - 6580 AA MALDEN

TEL. 024 - 358 65 14

FAX 024 - 358 70 79

www.wortelboer.ws

E-mail : info@wortelboer.ws

Pijpstoppers type STA 360

Bereik DN 12 - DN 2200 Max. testdruk tot 100 bar



Maat DN	Max. testdruk	Bereik I.D.
12	100 bar	12 - 14 mm.
14	100 bar	14 - 16 mm.
20	100 bar	20 - 25 mm.
25	100 bar	25 - 30 mm.
30	100 bar	30 - 35 mm.
35	100 bar	35 - 40 mm.
40	100 bar	40 - 45 mm.
50	100 bar	50 - 55 mm.
60	100 bar	60 - 65 mm.
65	100 bar	65 - 70 mm.
70	100 bar	70 - 75 mm.
75	100 bar	75 - 80 mm.
80	100 bar	76 - 92 mm.
90	100 bar	86 - 106 mm.
100	100 bar	96 - 112 mm.
110	95 bar	106 - 122 mm.
125	92 bar	121 - 137 mm.
140	90 bar	136 - 156 mm.

Maat DN	Max. testdruk	Bereik I.D.
150	90 bar	146 - 162 mm.
160	88 bar	156 - 172 mm.
175	85 bar	171 - 187 mm.
190	80 bar	186 - 206 mm.
200	80 bar	196 - 212 mm.
210	77 bar	206 - 222 mm.
225	75 bar	221 - 237 mm.
250	70 bar	246 - 263 mm.
260	65 bar	256 - 273 mm.
275	60 bar	271 - 288 mm.
300	60 bar	296 - 313 mm.
310	57 bar	306 - 323 mm.
350	50 bar	342 - 370 mm.
400	35 bar	392 - 420 mm.
450	30 bar	446 - 463 mm.
500	30 bar	492 - 520 mm.
600	25 bar	592 - 620 mm.

Grotere maten op aanvraag.

Als extra veiligheid vóór het afpersen van de leiding de persstop stempelen.

Afpersen uitsluitend met water!